

# Hillstone AX-Series:

## Application Delivery Controller (ADC)



Hillstone AX Series Application Delivery Controllers (ADCs) are the next generation of enterprise-class application delivery optimization products. The Hillstone ADC supports a full range of load balancing functions, including link load balancing (LLB), server load balancing (SLB) and global server load balancing (GSLB). In addition, the AX Series supports health checks for applications, servers and links, first-level network attack protection, SSL offload, application and data acceleration via caching, and more. The Hillstone ADC can greatly improve the availability and scalability of core applications and business platforms, and effectively improve the operational efficiency of enterprise data centers. Together with Hillstone security products such as next-generation firewalls, the Hillstone ADC can provide end-to-end application delivery and security capabilities for your applications and business operations.

Hillstone's ADC fully supports IPv6, high-performance clustering and carrier-grade high availability. It is widely used in server load balancing; traffic distribution and business continuity across multiple data centers; link optimization across multiple ISPs; CDN traffic management; and other application optimization and acceleration scenarios. The Hillstone ADC provides industry-leading solutions for government, finance, network operators, education, healthcare and other sectors.

## Product Highlights

### High-performance Server Load Balancing

Hillstone's AX Series provides server load balancing with high-capacity concurrent and new session processing capabilities. It intelligently adjusts traffic distribution based upon the health status of server nodes, and automatically completes switching to ensure the best user experience as well as application high availability. Hillstone's ADC utilizes Layer 4 to Layer 7 load balancing algorithms and load balancing based on domain names. Intelligent application identification based on characteristics, behavior and other information allows fine-tuning of performance and throughput to support employee productivity. It also supports application-layer content switching and rewrite to improve the availability of both servers and applications.

### Intelligent, Efficient and Dynamic Link Load Balancing

Hillstone's AX Series ADC offers enterprise-class link load balancing technology. It features an innovative adaptive link selection control algorithm that can detect link connectivity, bandwidth utilization, delay, packet loss and jitter in real time, and adjust the traffic forwarding rules based upon the actual link quality and performance. Using an intelligent closed loop, the best route can be selected in real time so that problems such as unbalanced link utilization, single point of failure, poor cross-ISP access, wastage of link resources, and other performance problems are eliminated. The Hillstone ADC supports multiple link load balancing modes such as ECMP, ISP routing, dynamic link switching, and application routing to ensure optimal link access and support employee productivity.

### High-performance SSL Offload for Secured Applications

Finance, healthcare, e-commerce and other applications are commonly secured via SSL encryption, which adds workload to servers that can impact performance and limit scalability. Hillstone's ADC supports SSL hardware acceleration technology that provides industry-leading 2048-bit SSL processing performance. By offloading SSL traffic to

the Hillstone ADC's dedicated SSL processing resources, the server workload is significantly reduced resulting in improved server performance and scalability.

### Full-featured IPv6

In addition to IPv6 support, the Hillstone ADC supports IPv6 application layer transformation technology to help IPv4 websites and networks seamlessly upgrade to or interoperate with IPv6. Through intelligent link processing technology, the addressing problem can be solved efficiently. The Hillstone ADC standard configuration comes with a 1T hard drive and supports log storage for the IPv6 application layer transformation.

### End-to-end Security Protection

Together with Hillstone Networks' next-generation firewalls, CloudEdge, CloudHive and other security products, the Hillstone ADC can provide end-to-end security protection capabilities from network access to data centers.

### SSL Traffic Orchestration

Hillstone's AX Series ADC provides SSL traffic orchestration function including SSL visualization, service chaining, and security device pooling, avoiding redundant encryption/decryption to maximize security devices' performance. With this feature set, users can easily configure SSL traffic service chains tailored to their specific business and traffic requirements. SSL traffic orchestration enables seamless scalability and enhances network elasticity, allowing organizations to adapt effortlessly to evolving demands, and effectively addressing security blind spots and mitigating single points of failure.

## Features

### Server Load Balancing

- L4 and L7 server load balancing
- HTTP content switching based on URL, HTTP header, cookie, source/destination IP, destination port, SSL/ TLS protocol and X509 certificate
- HTTP content rewriting, including external link rewriting
- Redirection for HTTP requests
- Supports Kubernetes
- Supports IPv6
- Supports HTTP2.0
- Supports WebSocket protocol
- Supports fast HTTP mode
- Supports ISO 8353 compatible message-based load balancing
- Supports RADIUS load balancing
- Supports MySQL load balancing with read/write splitting
- Supports node-based load balancing
- Supports HTTP Strict-Transport-Security (HSTS)
- Supports network mapping for visibility of relation between virtual servers, service pool, service pool members, and application servers
- Supports TCP template
- HTTPS virtual server supports HTTP redirection
- TOA supports format customization for source address insertion and extraction
- Support resetting the enabled functions when servers are down
- Virtual IP route advertisement over dynamic routing
- MySQL content switching based on source/ destination IP, destination port, database name, database account, and matching string
- Supports clustering up to 32 devices
- Supports SMTP/POP3/IMAP mail server, perform mail load balancing in three different modes: Plaintext, SSL, STARTTLS
- Supports connection number and connection rate limitation per virtual server/source IP
- Supports multiple certificates on a virtual server
- Supports verification of certificate chain integrity
- TCP Option extension supports IP version extraction and passthrough
- Supports displaying context correlation of L7 VS session
- Supports automatically convert iRules scripts (F5) to aRules scripts
- Supports load balancing and aRule programmable scripting for DNS

### Server Health Checks

- Predefined and custom health checks for ICMP, TCP, TCP-Echo, TCP-Half-Open, UDP, HTTP, HTTPS, HTTP2, SMTP, POP3, IMAP, DNS (UDP and TCP), FTP, SSL, Radius-Authentication, Radius-Accounting, WebSocket, WebSocket-SSL, SNMP-DCA, SNMP-DCA-Base, SIP-UDP, SIP-TCP, Passive-HTTP, Passive-TCP, MYSQL, MSSQL, Oracle, OceanBase, LDAP, WMI, TiDB, TDSQL-MySQL, Gauss-MySQL, and Third-Party
- HTTPS health check supports specifying TLS version, cipher suite and mutual authentication
- HTTP2 health check supports correlating to SSL template for HTTP2 ciphertext detection
- Supports server resource health check
- Supports passive health check
- Supports display and statistics of health check history
- Health check logs can be delivered through SMTP and SMS

### Server Session Persistence

- Source/ destination IP based and TOA based session persistence
- Supports session persistence for URL hash, HTTP/HTTPS, SMTP, POP3, HTTP header hash, session ID, request method, HTTP version, SIP CALL-ID, RDP, and Radius
- Supports session persistence for cookie including cookie hash, cookie insertion, cookie rewriting, and encrypted cookies
- Supports synchronization of session persistence table in a cluster
- Supports Set-cookie encryption and decryption
- Supports export of session persistence table
- Independent persistence profile for session persistence
- Session persistence table supports matching across virtual server + service pool, virtual IP, service pool, global, etc.

### Application Acceleration

- HTTP caching (jpg, doc, ppt, xls, html, css, js, pdf, swf, mp3, avi, flv, mp4)
- TCP connection multiplexing
- Supports TCP acceleration
- HTTP compression (doc, ppt, xls, html, css, js)

### SSL Inspection

- Software SSL offload; supported versions include SSLv2, SSLv3, TLS 1.0, TLS1.1, TLS1.2, TLS1.3
- SSL hardware acceleration
- Predefined or customized encryption algorithms with priorities
- SSL connection multiplexing
- Supports SSL proxy
- Works in conjunction with BDS, NIPS and WAF to identify encrypted traffic
- Supports mirroring decrypted SSL traffic

### SSL Traffic Orchestration

- Supports SSL orchestration for inbound traffic
- Supports decryption, interception and orchestration of TLS1.0, TLS1.1, and TLS1.2 traffic
- Supports interception and orchestration of non-SSL traffic
- Supports bypassing or dropping the in-progress traffic when security devices in the service chain fail
- Supports traffic distribution to security devices
- Supports health check on security devices in the service chain
- Supports traffic orchestration information log
- Supports statistics and display of traffic processed by security devices in the service chain, including new traffic, concurrent traffic, throughput, etc.
- Supports L2 transparent deployment mode
- Service chain selection based on content switching rules
- Supports delivering traffic orchestration policy via Restful API
- Supports automatically bypass traffic to backend service pools for SSL offloading when traffic decryption fails

### Link Load Balancing

- Supports IP address library and ISP address library with automatic update
- Policy routing supports domain name and geographic location routing
- Supports configuration of link priority and minimum active links
- Supports IPv6

### Global Server Load Balancing

- DNS server supports A, AAAA, NS, CNAME, PTR, MX, TXT, SRV
- DNS server supports recursive forwarding
- DNS server supports DNS Response Policy Zone (RPZ)
- DNS supports transparent proxy deployment
- Supports slave DNS server pool, synchronizing data from master DNS server automatically or manually
- Supports DNS-over-HTTPS (DoH)
- Inbound SmartDNS
- SmartDNS supports IP address library, ISP address library with automatic updates, overloaded link detection and dynamic proximity load balancing, service pool lists and service pool members
- SmartDNS host scheduling algorithms for service pool selection: Round Robin, Weighted Round Robin, Static Proximity, and Global Availability
- SmartDNS host scheduling algorithms for service pool member selection: Round Robin, Weighted Round Robin, IP Hash, Static Proximity, All IPs, Priority, Dynamic Ratio, Global Availability, Backup IP
- SmartDNS supports configuration of multiple served regions per service pool/server (exclusion addresses/regions is allowed)
- Supports clustering multiple devices
- Supports monitoring of virtual server health status
- DNS resolution supports white-and-black list and rate limiting control
- Resource record types include A, AAAA, CNAME, MX, SRV

## Features (continued)

- Supports configuring root DNS server
- Supports DNSSEC
- Supports Transaction Signature (TSIG)
- DNS cache supports setting Time-to-Live (TTL), clearing, viewing, and tracking hit statistic
- Supports user-defined syslog format
- Aligned with F5: Optional number of GSLB deployment per data center; Each data center can be enabled/disabled

### System Management

- System management via WebUI, Console, Web Console, Telnet and SSH
- Restful API supports
- Supports Ansible for automated operation and maintenance management
- Role-based authorization of administrators, auditors and operators
- Access control on the administrator address for remote management
- Supports WebUI administrators to bind to trust domain, and certificate authentication for administrators
- Configuration for password complexity and minimum length restrictions
- Supports SNTP, and synchronization of system time from multiple NTP servers
- Supports multiple configuration files and configuration file backup and recovery
- Supports hping, tcpdump and curl operation and maintenance tools
- Supports SLB objects partition for administration with different privileges
- Supports continuous system operation during hard disk drive failures
- Supports multi-version image deployment (up to 3 images)
- Supports software and hardware maintenance through soft isolation
- Supports operation and maintenance tools including netstat/ echo/ top, and restart process command
- Download and export configuration files, syslog, and packet capture files through SFTP client

### Application Identification

- Application identification based on application characteristics, behavior and related information
- Multi-dimensional application definitions
- Thousands of application signatures
- Application signature database updated in real-time

### Log and Monitoring


- Supports a variety of log types, including event logs, network logs, configuration logs, NAT logs, SLB logs, health check logs, etc.
- Supports queries for L4/L7 load balancing logs and global load balancing logs within past hour, past day, past week, and custom time spans up to one week (a maximum of 100,000 entries can be exported)
- Log storage in both local device and server
- Email alarms and log alarms
- Real-time WebUI display of system resource utilization and hardware status
- Monitoring and graphical display of server load balancing status, including traffic, new connections, concurrent connections (established concurrent connections, client concurrent connections, server concurrent connections), requests per second and CPU utilization of virtual servers; supports displaying traffic, new connections, concurrent connections, requests per second, and other historical real-time information of each real server in the server pool
- Supports displaying historical information of the operational status of virtual servers, server pool members, and real servers
- Supports displaying statistical information of hit per second, total hit count, and last hit time for HTTP content switching
- Device status monitoring on mobile devices via CloudView
- Supports forwarding SLB log, health check binary log to HSA
- Supports multi-dimensional statistics and monitoring of HTTP traffic, including URL, client IP, response code, HTTP method, and user agent
- Supports reporting with multiple statistics, including business processing status, load balancing data, etc.
- Supports DNS traffic visualization based on domain/IP, displaying the top 10

- total requests, successful resolutions, and failed resolutions
- Supports displaying historical statistical data of DNS traffic for the last hour
- Supports displaying top 10 users by traffic, concurrent connections, and session rate
- Link Aggregation Control Protocol (LACP) supports passive mode
- Supports configuration comparison

### Deployment and Network Configuration

- Supports DNS proxy
- DNS proxy blacklist and whitelist
- Supports Botnet C&C prevention, including domain reputation library and DNS sinkhole capability
- Deployment via one-arm reverse proxy, routing, transparent, or DSR
- Supports static routing, ISP routing, policy routing, and RIP dynamic routing protocol, and supports import of ISP information
- HA AP mode, supports synchronization of configuration (auto/manual), session, health checks, PKI synchronization
- Policy control
- VSYS
- Supports AWS, Azure, Huawei Cloud and Alibaba Cloud (manual deployment only)
- Supports LMS centralized authorization
- Supports VMware / KVM / Xen / Hyper-V virtualization deployment
- QoS
- Session limiting
- Supports anti-DDoS
- Supports centralized management
- Supports programmable script aRules
- Supports SNMP
- Support setting configuration validity scope (local device/ within the cluster)
- Supports cluster manual/automatic configuration synchronization
- Supports cluster bi-directional configuration synchronization: synchronize configuration changes made on any device to the entire cluster or to specific devices within the cluster
- Supports F5 configuration migration tools:
  - F5 LTM module configuration conversion
  - Import and conversion of F5 UCS configuration files without decompression
  - Configuration comparison
  - Output conversion results/ error messages/ operation logs

# Specifications

	SG-6000-AX120S-IN	SG-6000-AX220S-IN	SG-6000-AX320S-IN	SG-6000-AX520S-IN
				
<b>L4 Throughput</b>	3 Gbps	16 Gbps	18 Gbps	30 Gbps
<b>L4 Connections/s</b>	40,000	110,000	120,000	270,000
<b>L7 HTTP Throughput</b>	1.5 Gbps	5 Gbps	6 Gbps	10 Gbps
<b>L7 HTTP Requests/s (RPS)</b>	50,000	130,000	130,000	320,000
<b>Concurrent Connections</b>	1 Million	1 Million	3 Million	10 Million
<b>RSA 2K SSL (CPS) <sup>(1)</sup></b>	200/950	600/3,500	600/3,500	1,800/8,000
<b>RSA 2K SSL (RPS) <sup>(2)</sup></b>	5,000	17,000	17,000	52,000
<b>RSA 2K SSL Throughput <sup>(3)</sup></b>	0.4 Gbps	1.5 Gbps	1.8 Gbps	4 Gbps
<b>SSL Acceleration Technology</b>	Hardware	Hardware	Hardware	Hardware
<b>DNS (QPS)</b>	19,000	39,000	40,000	95,000
<b>Storage</b>	480 GB SSD	480 GB SSD	480 GB SSD	960 GB SSD
<b>Memory</b>	4 GB	4 GB	8 GB	16 GB
<b>Management Ports</b>	2 × USB Ports, 1 × MGT Port, 1 × Console Port	2 × USB Ports, 1 × MGT Port, 1 × Console Port	2 × USB Ports, 1 × MGT Port, 1 × HA, 1 × Console Port	2 × USB Ports, 1 × MGT Port, 1 × HA, 1 × Console Port
<b>GE Ports</b>	8 (includes 1 pair bypass)	8 (includes 1 pair bypass)	16 (includes 2 pairs bypass)	16 (includes 2 pairs bypass)
<b>GE Ports (SFP)</b>	N/A	8	8	8
<b>10GE (SFP+)</b>	N/A	2	2	2, up to 6 with expansion module
<b>40GE Ports (QSFP+)</b>	N/A	N/A	N/A	0, up to 2 with expansion module
<b>Available Slots for Expansion Modules</b>	N/A	N/A	N/A	1
<b>Expansion Module Option</b>	N/A	N/A	N/A	IOC-A-4SFP+IN IOC-A-2QSFP+IN IOC-A-2MM-BE-IN IOC-A-2SM-BE-IN
<b>Power Supply</b>	Single/ Dual AC, 100-240V	Single/ Dual AC, 100-240V	Single/ Dual AC, 100-240V	Dual AC, 100-240V, redundant hot-swappable
<b>Frequency</b>	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
<b>Average Power</b>	50W	50W	100W	100W
<b>Height</b>	1U	1U	1U	1U
<b>Dimension (W×D×H)</b>	17.2 x 12.6 x 1.7 in (436 x 320 x 44mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)
<b>Net Weight</b>	8.6 lb (3.9 kg)	9 lb (4.1 kg)	13.2 lb (6 kg)	15 lb (6.8 kg)
<b>Gross Weight</b>	14.3 lb (6.5 kg)	17 lb (7.7 kg)	20.7 lb (9.4 kg)	26 lb (11.8 kg)
<b>Operating Temperature</b>	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)
<b>Storage Temperature</b>	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)
<b>Allowed Relative Humidity</b>	10-95%, non-condensing	5-85%, non-condensing	10-95%, non-condensing	10-95%, non-condensing

# Specifications (Continued)

	SG-6000-AX1200S-IN	SG-6000-AX2000-IN	SG-6000-AX2000S-IN	SG-6000-AX2200S-IN	SG-6000-AX3200S-IN
<b>L4 Throughput</b>	70 Gbps	85 Gbps	85 Gbps	85 Gbps	90 Gbps
<b>L4 Connections/s</b>	700,000	1 Million	1 Million	1 Million	1.3 Million
<b>L7 HTTP Throughput</b>	20 Gbps	30 Gbps	30 Gbps	30 Gbps	35 Gbps
<b>L7 HTTP Requests/s (RPS)</b>	850,000	1.2 Million	1.2 Million	1.2 Million	1.45 Million
<b>Concurrent Connections</b>	20 Million	40 Million	40 Million	40 Million	40 Million
<b>RSA 2K SSL (CPS) <sup>(1)</sup></b>	4,200/23,000	5,000	25,000	8,000/40,000	9,000/46,000
<b>RSA 2K SSL (RPS) <sup>(2)</sup></b>	130,000	120,000	140,000	200,000	250,000
<b>RSA 2K SSL Throughput <sup>(3)</sup></b>	8 Gbps	5.5 Gbps	6 Gbps	12 Gbps	15 Gbps
<b>SSL Acceleration Technology</b>	Hardware	Software	Hardware	Hardware	Hardware
<b>DNS (QPS)</b>	240,000	350,000	350,000	420,000	460,000
<b>Storage</b>	960 GB SSD	1TB HDD	1TB HDD	960 GB SSD	960 GB SSD
<b>Memory</b>	32 GB	64 GB	64 GB	64 GB	64 GB
<b>Management Ports</b>	2 x USB Ports, 1 x MGT Port, 2 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port	2 x USB Ports, 1 x MGT Port, 1 x HA, 1 x Console Port
<b>GE Ports</b>	8 (includes 2 pairs bypass)	2 (includes 2 MGT ports), up to 34 ports with expansion modules	2 (includes 2 MGT ports), up to 34 ports with expansion modules	8 (includes 4 pairs bypass)	8 (includes 4 pairs bypass)
<b>GE Ports (SFP)</b>	16	0, up to 32 with expansion module	0, up to 32 with expansion module	0	0
<b>10GE(SFP+)</b>	6, up to 10 with expansion module	0, up to 16 with expansion module	0, up to 16 with expansion module	16, up to 20 with expansion module	16, up to 20 with expansion module
<b>40GE Ports (QSFP+)</b>	0, up to 2 with expansion module	0, up to 8 with expansion module	0, up to 8 with expansion module	2, up to 4 with expansion module	2, up to 4 with expansion module
<b>Available Slots for Expansion Modules</b>	1	4	4	1	1
<b>Expansion Module Option</b>	IOC-AX-4SFP+IN IOC-AX-2QSFP+IN IOC-AX-2MM-BE-IN IOC-AX-2SM-BE-IN	IOC-AX-4GE-B-H-IN, IOC-AX-4SFP-H-IN, IOC-AX-8GE-B-H-IN, IOC-AX-8SFP-H-IN, IOC-AX-4GE4SFP-H-IN, IOC-AX-2SFP+H-IN, IOC-AX-4SFP+H-IN, IOC-AX-2QSFP+H-IN	IOC-AX-4GE-B-H-IN, IOC-AX-4SFP-H-IN, IOC-AX-8GE-B-H-IN, IOC-AX-8SFP-H-IN, IOC-AX-4GE4SFP-H-IN, IOC-AX-2SFP+H-IN, IOC-AX-4SFP+H-IN, IOC-AX-2QSFP+H-IN	IOC-A-4SFP+IN IOC-A-2QSFP+IN IOC-A-2MM-BE-IN IOC-A-2SM-BE-IN	IOC-A-4SFP+IN IOC-A-2QSFP+IN IOC-A-2MM-BE-IN IOC-A-2SM-BE-IN
<b>Power Supply</b>	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable	Dual AC, 100-240V, redundant hot-swappable
<b>Frequency</b>	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
<b>Average Power</b>	289W	550W	550W	382W	382W
<b>Height</b>	1U	2U	2U	1U	1U
<b>Dimension (WxDxH)</b>	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)	21.7 x 17.3 x 3.5 in (550 x 440 x 88mm)	21.7 x 17.3 x 3.5 in (550 x 440 x 88mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)	17.2 x 17.2 x 1.7 in (436 x 437 x 44mm)
<b>Net Weight</b>	22.5 lb (10.2 kg)	50.7 lb (23 kg)	52.9 lb (24 kg)	22.5 lb (10.2 kg)	22.5 lb (10.2 kg)
<b>Gross Weight</b>	32.6 lb (14.8 kg)	61.7 lb (28 kg)	63.9 lb (29 kg)	32.6 lb (14.8 kg)	32.6 lb (14.8 kg)
<b>Operating Temperature</b>	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)	32-104 °F (0-40 °C)
<b>Storage Temperature</b>	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)	-40-158 °F (-40-70 °C)
<b>Allowed Relative Humidity</b>	10-95%, non-condensing	5-90%, non-condensing	5-90%, non-condensing	10-95%, non-condensing	10-95%, non-condensing

## Specifications: Virtual Appliance

	SG-6000-AX02-IN	SG-6000-AX04-IN	SG-6000-AX08-IN	SG-6000-AX12-IN
CPU	2 Core	4 Core	8 Core	12 Core
HDD (min., max.)	20 GB, 1 TB	20 GB, 1 TB	20 GB, 1 TB	20 GB, 1 TB
Memory	4 GB	8 GB	16 GB	24 GB
Maximum Interfaces	10	10	10	10
L4 Throughput (KVM SRIOV)	5 Gbps	10 Gbps	20 Gbps	30 Gbps
L4 Throughput (Virtio)	2 Gbps	2 Gbps	2 Gbps	2 Gbps
L7 HTTP Throughput (KVM SRIOV)	4 Gbps	7.5 Gbps	15 Gbps	22 Gbps
L7 HTTP Throughput (Virtio)	2 Gbps	2 Gbps	2 Gbps	2 Gbps
L4 Connections/s	120,000	160,000	400,000	550,000
L7 HTTP Connections/s	60,000	150,000	300,000	450,000
Concurrent Connections	1 Million	3 Million	6 Million	9 Million
ECDHE RSA 2K SSL (CPS) (KVM SRIOV) <sup>(1)</sup>	700	1,500	4,000	6,500
ECDHE RSA 2K SSL (CPS) (Virtio)	700	700	700	700
ECDHE RSA 2K SSL (RPS) (KVM SRIOV) <sup>(2)</sup>	10,000	20,000	55,000	85,000
ECDHE RSA 2K SSL (RPS) (Virtio)	9,500	9,500	9,500	9,500
ECDHE RSA 2K SSL Throughput (KVM SRIOV) <sup>(3)</sup>	900 Mbps	1.5 Gbps	4 Gbps	4.4 Gbps
ECDHE RSA 2K SSL Throughput (Virtio)	800 Mbps	800 Mbps	800 Mbps	800 Mbps

## Module Options

Module	IOC-AX-4GE-B-H-IN	IOC-AX-4SFP-H-IN	IOC-AX-8GE-B-H-IN	IOC-AX-8SFP-H-IN	IOC-AX-4GE4SFP-H-IN	IOC-AX-2SFP+-H-IN
I/O Ports	4 × GE Bypass Ports	4 × SFP Ports	8 × GE Bypass Ports	8 × SFP Ports	4 × GE and 4 × SFP Ports	2 × SFP+ Ports
Dimension	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)
Weight	0.33 lb (0.15 kg)	0.33 lb (0.15 kg)	0.55 lb (0.25 kg)	0.55 lb (0.25 kg)	0.55 lb (0.25 kg)	0.33 lb (0.15 kg)

Module	IOC-AX-4SFP+-H-IN	IOC-AX-2QSFP+-H-IN	IOC-A-4SFP+-IN	IOC-A-2QSFP+-IN	IOC-A-2MM-BE-IN	IOC-A-2SM-BE-IN
I/O Ports	4 × SFP+ Ports	2 × QSFP+ Ports	4 × SFP+, SFP+ module not included	2 × QSFP+	4 × SFP, MM bypass (2 pairs of bypass ports)	4 × SFP, SM bypass (2 pairs of bypass ports)
Dimension	1U (Occupies 1 generic slot)	1U (Occupies 1 generic slot)	1U	1U	1U	1U
Weight	0.44 lb (0.2 kg)	N/A	2.09 lb (0.96 kg)	2.09 lb (0.96 kg)	2.09 lb (0.96 kg)	2.09 lb (0.96 kg)

### NOTES:

- (1) Connection: Request=1:1; The data of AX120S-IN/AX220S-IN/AX320-IN/AX520S-IN/AX1200S-IN/AX2200S-IN/AX3200S-IN can be increased to 950/3,500/3,500/8,000/23,000/40,000/46,000 with SSL license;
- (2) In the test, Requests Per Second uses Maximum Possible; Connection: Request=1: N;
- (3) The RSA key length is 2048Bit, and the encryption suite is AES256-SHA256



Distributeur à valeur ajoutée

## VOTRE PARTENAIRE TECHNOLOGIQUE POUR DES INFRASTRUCTURES IT SÉCURISÉES ET PERFORMANTES



**EXPERTISE**  
Des solutions adaptées à chaque environnement



**CONFIANCE**  
Un partenaire fiable à vos côtés



**PERFORMANCE**  
Des infrastructures sécurisées et évolutives



**SUPPORT**  
Un accompagnement technique de qualité



Des solutions IT innovantes pour un monde connecté et sécurisé



**WIRELESS RADIO**  
Connectivité sans fil haute performance



**RÉSEAUX & SÉCURITÉ IT**  
Des réseaux fiables et sécurisés



**VIRTUALISATION CLOUD**  
Des solutions Cloud flexibles et évolutives



**CYBERSECURITY**  
Protéger vos données et vos systèmes



**VIDÉO PROTECTION**  
Solutions de vidéosurveillance intelligentes



**HCI STOCKAGE SAUVEGARDE**  
Stockage, sauvegarde et haute disponibilité

SOLUTIONS IT | CYBERSÉCURITÉ | CLOUD | INFRASTRUCTURE RÉSEAU | STOCKAGE | PROTECTION



**Vous accompagne**



[www.hafs-networks.com](http://www.hafs-networks.com)  
Visitez notre site web



[sales-ci@hafs-networks.com](mailto:sales-ci@hafs-networks.com)  
Envoyez-nous un e-mail



(+225) 07 69 32 13 55  
Contact commercial 1



(+225) 07 59 05 85 82  
Contact commercial 2

Distributeur à Valeur Ajoutée de Solutions de Cybersécurité | Réseaux | Wi-Fi | HCI/Sauvegarde

